

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1. (currently amended) A method for ~~managing partitioning~~ container-managed state for a Java based application, comprising the operations of:

classifying individual entity bean objects according to a particular state management type, the state management type being one of a recoverable state or a non-recoverable state, the recoverable state being one of a memory replicated state management type and ~~or~~ a disk replicated state management type;

providing a plurality of state objects, each state object storing a state of a corresponding entity bean object within a memory address space of a Java server process, wherein each state object is associated with the state management type of the corresponding entity bean object; and

providing state management for each entity bean object using a state object associated with the state management type corresponding to the respective entity bean object, the providing state management being based separately on each different ~~the~~ state management type and on those that is associated with the state objects ~~object~~ corresponding to the different state management type the respective entity bean object , the providing state management comprising replicating each one of the plurality of state objects in a state server, a different one of the state servers ~~server for a particular state object~~ being dedicated to a particular one of the state management types ~~type that corresponds to the state management type that is associated with the particular state object~~ a different one of the state servers being provided for each different recoverable state management type.

Claims 2-3. (canceled)

Claim 4. (previously amended) A method as recited in claim 1, further comprising the operation of grouping the state objects based on the type of state management to which the corresponding entity bean object is classified.

Claim 5. (currently amended) A method as recited in claim 4, wherein the state management type into which a group of state objects are grouped identifies a policy for replication of the group of state objects to the dedicated state server that is dedicated to the different ~~particular~~ state management type corresponding to the group .

Claim 6. (Original) A method as recited in claim 4, wherein the state management type identifies a policy for migration of a state object from one server process to another server process.

Claim 7. (Original) A method as recited in claim 1, further comprising the operation of managing checkpoints using the state objects.

Claim 8. (Original) A method as recited in claim 1, further comprising the operation of performing lock management using the state objects.

Claim 9. (currently amended) A method for managing ~~partitioning~~ container-managed state for a Java application, comprising the operations of:

partitioning individual entity bean objects of the Java application into state partitions, wherein the state partitions manage concurrency for the Java application, the partitioning being by storing state of each particular entity bean object in a state object dedicated to a state management type ~~objects~~ corresponding to the state management type of the particular entity bean object ~~objects~~;

classifying individual state ~~entity bean~~ objects within each state partition using state management units, wherein each particular state management unit is a collection of the state objects corresponding to one particular state management type for recoverable and migration capable state of the respective corresponding particular entity bean objects; and

replicating each particular state management unit in one of a plurality of state servers according to the particular state management type that corresponds to the particular state objects classified in the particular state management unit.

Claims 10-12. (canceled)

Claim 13. (previously amended) A method as recited in claim 9, further comprising the operation of using a control module to manage dynamic partitioning of the state of the application via the state partitions and the state management units.

Claim 14. (original) A method as recited in claim 13, wherein the state partitions and state management units are modular.

Claim 15. (original) A method as recited in claim 14, wherein additional state management types for the state management units can be defined.

Claim 16. (original) A method as recited in claim 15, wherein each state partition serializes transactions for entity bean objects within a particular state partition.

Claim 17. (original) A method as recited in claim 16, wherein each state partition allows only one concurrent transaction to be performed on the entity bean objects within the particular state partition during a given time period.

Claim 18. (currently amended) A system for managing ~~partitioning~~ container-managed state for a Java based application, comprising:

an application having a plurality of entity bean objects, each entity bean object comprising a state management type, the state management type being one of a recoverable state or a non-recoverable state, the recoverable state being one of a memory replicated state management type and ~~or~~ a disk replicated state management type;

a plurality of state objects, each state object storing a state of a corresponding entity bean object within a memory address space of a Java server process, wherein each state object is associated with a particular state management type of the corresponding entity bean object;

a plurality of state management units that classify the state objects, a particular state object being classified into a particular state management unit based on the particular state management type of the corresponding entity bean object, wherein the state management units facilitate state management for each entity bean object;

a state server dedicated to each state management type, the state management type identifying a policy for replication of a state object to a state server dedicated to a particular state management type and a policy for migration of a state object from one server process to another server process; and

a replicated state manager configured to replicate a particular state management unit to the state server that is dedicated to the particular state management type of the particular state object that is classified into the particular state management unit to be replicated.

Claim 19. (original) A system as recited in claim 18, wherein the entity bean objects of the application are partitioned into state partitions during pre-deployment.

Claim 20. (original) A system as recited in claim 19, further comprising a repository that maintains state partition specifications for the state partitions.

Claim 21. (original) A system as recited in claim 20, wherein the repository manages replication and migration of state of the Java application during runtime.

Claims 22-24. (canceled)

Claim 25. (previously amended) A system as recited in claim 18, wherein the replicated state manager is further configured to replicate a particular state object from the one server process to the other server process according to the policy for migration .